



## Alice in Wonderland Charm Bracelet

© Sherri Haab Designs 2010

### Supplies Needed:

- “Alice” collage sheet images (Sherri Haab Designs)
- Scissors
- Pewter bezels (Sherri Haab Designs)
- Flat brush
- Mod Podge® decoupage medium
- Waxed paper
- 2-part epoxy resin - Envirotex Lite (Sherri Haab Designs)
- Mixing cups (Sherri Haab Designs)
- Stir stick, toothpicks
- Heat embossing tool
- Silver colored charm bracelet with clasp (Sherri Haab Designs)
- Silver jump rings
- Bead dangles and accent beads
- Head pins
- Round-nose pliers
- 2 chain-nose pliers
- Wire cutters



Find all available supplies for this project at:

<http://www.sherrahaab-shop.com/jewelry-supplies/alicebracelet.html>

### Steps:

1. Cut the images to fit the bezels. Press around the edges of the paper with your fingers to emboss the paper with the edge of the bezel, which will give you a line to cut on.
2. Cut around this embossed line and check the fit of the paper for the bezel. Trim the paper a little more if necessary until the image fits.
3. To seal, coat the back, front, and edges of the paper with Mod Podge using a flat brush. If the paper isn't properly sealed, the resin will stain the paper. Work on waxed paper to keep the paper from sticking to your work surface as you coat the paper. Let the paper images dry thoroughly.
4. Press the image into the bezel. Use a toothpick to tuck the paper in around the inside of the bezel wall. Make sure there are no air bubbles under the paper.
5. Mix the 2-part epoxy resin in a mixing cup as directed on box.
6. Use a wood stir stick to layer the epoxy resin over the images in the bezels, filling the bezels to the top. Use a rubber stamp heat embossing tool to remove any bubbles in the resin. Do not use an industrial type heat gun as these run too hot. Let the resin cure in a warm place overnight or until no longer tacky.
7. After the epoxy resin is cured, attach the bezels to the chain with jump rings using pliers.
8. Add beads with head pins if you want to add dangles to hang from some of the bezels. Form a loop with round nose pliers at the top of the bead, which is threaded on the pin, attach to the bezel and then wrap the wire at the base of the loop. Cut off the excess wire close to the wrapped section with wire cutters.